



COSMIC

Series 0412 · Cosmic system · Medium format

A1 · EN 13501-1

COSMIC SYSTEM



COSMIC — 3D gypsum wall panel, supplied white and painted on site.

KEY FACTS — PER PANEL

PANEL SIZE

300 × 300 MM

THICKNESS

30 MM

WEIGHT PER PANEL

2.5 KG

COVERAGE PER PANEL

0.09 M²

SUPPLIED AS

SINGLE PANEL

SERIES

0412

MATERIAL & COMPOSITION

- Reinforced gypsum fibre board — EN 15283-2:2008+A1:2009
- Mineral composition · no harmful additives
- Mean density 1130 kg/m³ (EN 15283-2)
- Supplied white, unfinished — painted on site in any colour
- For dry interior walls and ceilings


REACTION TO FIRE

A1

Classified **A1 (EN 13501-1)** — the highest fire rating under European fire safety standards. Non-combustible.

Classification report No. 1871-CPR-RtF-921 · CTEC Ltd, Notified Body 1871 · AVCP System 3 · Tested to EN ISO 1182 / EN ISO 1716

IN DETAIL



COSMIC · PRODUCT TILE



COSMIC · INTERIOR

COSMIC SYSTEM — WITH OR WITHOUT LED

COSMIC is available in dedicated LED and no-LED versions (Medium format). This sheet covers the no-LED version; the LED version is listed separately on kandes.eu.

INSTALLATION SUMMARY

- 1 **Acclimatise.** Keep panels in their original packaging, stored vertically as delivered, for 24 hours in the room before installation. Unpack immediately before installing.
- 2 **Bond.** Fix to a firm, level, clean substrate with gypsum-based adhesive; mechanical fixing where required.
- 3 **Fill joints.** Use a fine, soft filler paste — not the adhesive gypsum putty.
- 4 **Finish.** Sand and prime the filled joints.
- 5 **Paint.** On site, in any colour.

Any skilled tiler or plasterer can handle the installation.

STORAGE & HANDLING

- Store vertically in the original packaging, as delivered on the pallet — never flat
- Dry interior storage, 15–25 °C, 40–60 % RH
- Protect from moisture and direct water contact

DELIVERY

IN STOCK
HANDLING 1–3 BUSINESS DAYS
EU DELIVERY 5–10 BUSINESS DAYS

Custom requests may require additional lead time.

RELATED DOCUMENTATION

[Declaration of Performance \(DoP\)](#)

[Technical Data Sheet — product family](#)

[Compliance Summary Report](#)

[Installation guide & videos](#)

Request the complete document pack via “Get the spec sheets” on the product page, or write to info@kandes.ch. The EN 13501-1 fire classification report (No. 1871-CPR-RtF-921) is available on request.